

## CALLE

207266A 28" LED Chandelier

## FINISHES

207266A  
Brass

## PRODUCT ATTRIBUTES

|                  |                        |
|------------------|------------------------|
| Fixture Finish   | Brass                  |
| Fixture Material | Steel                  |
| Shade Finish     | Gold Leaf Hand-Pressed |
| Shade Material   | Glass                  |
| Accessory Stems  | 208081A                |
| UPC Code         | 9008606385232          |
| Warranty         | 5 Years                |

## DIMENSIONS

|                     |                                                   |
|---------------------|---------------------------------------------------|
| Fixture (W x D x H) | 28" (710 mm) x 28" (710 mm) x 42.5" (1080 mm)     |
| Shade (W x D x H)   | 1.75" (44 mm) x 1.75" (44 mm) x 13.75" (350 mm)   |
| Canopy (W x D x H)  | 6.25" (160 mm) x 6.25" (160 mm) x 1.5" (40 mm)    |
| Canopy Shape        | Round                                             |
| Min. Height         | 49.5" (1256 mm)                                   |
| Max. Height         | 79.5" (2017 mm)                                   |
| Wire                | 144" (3660 mm)                                    |
| Rods                | 2 x 3" (76 mm), 2 x 6" (152 mm), 3 x 12" (305 mm) |
| Weight              | 22.05 LBS10 KG                                    |

## LIGHT SOURCE

|                       |                      |
|-----------------------|----------------------|
| Light Source          | 30W LED (Integrated) |
| Color Temp. (K)       | 3000K                |
| Initial Lumens (lm)   | 2841                 |
| Delivered Lumens (lm) | 738                  |
| CRI (Ra)              | >80                  |
| Lifetime Hours        | 30000                |
| Dimmable              | Yes                  |

## SPECIFICATIONS

|                    |                                           |                  |     |
|--------------------|-------------------------------------------|------------------|-----|
| Input Voltage      | 120V, 60Hz                                | Output Voltage   | 36V |
| System Type        | Hardwired                                 |                  |     |
| Certifications     | cETLus, FCC/ICES 005                      |                  |     |
| Location Rating    | Dry                                       |                  |     |
| Mounting Direction | Ceiling                                   |                  |     |
| Sloped Ceiling     | Yes                                       | Max. Slope Angle | 15° |
| Light Direction    | Ambient                                   |                  |     |
| Adjustability      | Adjustable Height - Rods, Adjustable Arms |                  |     |