

## COURTNEY

207414A 48" 5CCT LED Linear Chandelier

## FINISHES

207414A  
Textured Black

## PRODUCT ATTRIBUTES

|                   |                    |
|-------------------|--------------------|
| Fixture Finish    | Textured Black     |
| Fixture Material  | Aluminum           |
| Diffuser Finish   | Clear Water, White |
| Diffuser Material | Glass, Acrylic     |
| Switch Type       | 5CCT Slide Switch  |
| Accessory Stems   | 208065A            |
| UPC Code          | 9008606385904      |
| Warranty          | 5 Years            |

## DIMENSIONS

|                     |                                                   |
|---------------------|---------------------------------------------------|
| Fixture (W x D x H) | 48" (1220 mm) x 3.5" (89 mm) x 4" (103 mm)        |
| Canopy (W x D x H)  | 15.75" (400 mm) x 4.75" (120 mm) x 1.5" (37 mm)   |
| Canopy Shape        | Rectangle                                         |
| Min. Height         | 9.75" (247 mm)                                    |
| Max. Height         | 60.75" (1543 mm)                                  |
| Wire                | 144" (3660 mm)                                    |
| Rods                | 4 x 3" (76 mm), 4 x 6" (152 mm), 6 x 12" (305 mm) |
| Weight              | 32.39 LBS14.69 KG                                 |

## LIGHT SOURCE

|                       |                                   |
|-----------------------|-----------------------------------|
| Light Source          | 83W LED (Integrated)              |
| Color Temp. (K)       | 2700K, 3000K, 3500K, 4000K, 5000K |
| Initial Lumens (lm)   | 9754                              |
| Delivered Lumens (lm) | 2476                              |
| CRI (Ra)              | >80                               |
| Lifetime Hours        | 36000 (L70)                       |
| Dimmable              | Yes                               |

## SPECIFICATIONS

|                    |                          |                  |     |
|--------------------|--------------------------|------------------|-----|
| Input Voltage      | 120-277V, 60Hz           | Output Voltage   | 36V |
| System Type        | Hardwired                |                  |     |
| Certifications     | cETLus, FCC/ICES 005     |                  |     |
| Location Rating    | Dry                      |                  |     |
| Mounting Direction | Ceiling                  |                  |     |
| Sloped Ceiling     | Yes                      | Max. Slope Angle | 16° |
| Light Direction    | Multiple                 |                  |     |
| Adjustability      | Adjustable Height - Rods |                  |     |