

## RISTRETTO

208112A 50" LED Linear Chandelier

## FINISHES

208112A  
Brushed Nickel

## PRODUCT ATTRIBUTES

|                  |                     |
|------------------|---------------------|
| Fixture Finish   | Brushed Nickel      |
| Fixture Material | Steel, Aluminum     |
| Shade Finish     | Clear Ribbed, White |
| Shade Material   | Acrylic             |
| Accessory Stems  | 208077A             |
| UPC Code         | 9008606403783       |
| Warranty         | 5 Years             |

## DIMENSIONS

|                     |                                                   |
|---------------------|---------------------------------------------------|
| Fixture (W x D x H) | 50" (1270 mm) x 5" (125 mm) x 10" (253 mm)        |
| Shade (W x D x H)   | 2.25" (55 mm) x 2.25" (55 mm) x 6.25" (156 mm)    |
| Canopy (W x D x H)  | 9" (229 mm) x 4.5" (114 mm) x 1.5" (40 mm)        |
| Canopy Shape        | Rectangle                                         |
| Min. Height         | 20.25" (514 mm)                                   |
| Max. Height         | 62.25" (1581 mm)                                  |
| Wire                | 144" (3660 mm)                                    |
| Rods                | 4 x 3" (76 mm), 4 x 6" (152 mm), 6 x 12" (305 mm) |
| Weight              | 17.64 LBS8 KG                                     |

## LIGHT SOURCE

|                       |                      |
|-----------------------|----------------------|
| Light Source          | 36W LED (Integrated) |
| Color Temp. (K)       | 3000K                |
| Initial Lumens (lm)   | 4584                 |
| Delivered Lumens (lm) | 2102                 |
| CRI (Ra)              | >90                  |
| Lifetime Hours        | 50000 (L70)          |
| Dimmable              | Yes                  |

## SPECIFICATIONS

|                    |                          |                  |     |
|--------------------|--------------------------|------------------|-----|
| Input Voltage      | 120-277V, 60Hz           | Output Voltage   | 36V |
| System Type        | Hardwired                |                  |     |
| Certifications     | cETLus, FCC/ICES 005     |                  |     |
| Location Rating    | Dry                      |                  |     |
| Mounting Direction | Ceiling                  |                  |     |
| Sloped Ceiling     | Yes                      | Max. Slope Angle | 90° |
| Light Direction    | Ambient                  |                  |     |
| Adjustability      | Adjustable Height - Rods |                  |     |